

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924 (ChemTel)
International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: NON-CHLORINATED BRAKE & PARTS CLEANER 14.5 OZ
Item No: 82220
Product Type: Aerosol cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
ACETONE 67-64-1	50-60	500 ppm	1000 ppm; 2400 mg/m ³
METHANOL 67-56-1	20-30	200 ppm	200 ppm; 260 mg/m ³
HEPTANE 142-82-5	10-20	400 ppm	500 ppm; 2000 mg/m ³
XYLENE 1330-20-7	<10	100 ppm	100 ppm; 435 mg/m ³
CARBON DIOXIDE 124-38-9	<10	5000 ppm	5000 ppm; 9000 mg/m ³

3. HAZARDS IDENTIFICATION

Toxicity: Danger: Poison. Methanol may cause blindness or death if swallowed. Aspiration hazard if swallowed. May cause eye, skin and respiratory irritation. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss. Intentional misuse by concentrating and inhaling the vapor may be harmful or fatal.

Primary Routes of Entry: Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure: Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. May cause redness to eyes and irritation to nasal passages.

Component	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
ACETONE 67-64-1	50-60		A4 - Not Classifiable as a Human Carcinogen	
XYLENE 1330-20-7	<10	male rat-no evidence; female rat-no evidence; male mice-no evidence; female mice-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3: Monograph 71, 1999; Monograph 47, 1989

Aggravated Medical Condition: Heart disease, respiratory disorders, liver and kidney diseases, amenia, rhythm disorders of the heart.

4. FIRST AID MEASURES

Ingestion: Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Oxygen or artificial respiration if needed. Obtain medical attention.

Skin Contact: Wash off with soap and water. Remove contaminated clothing and launder before reuse. If skin irritation persists, call a physician.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): Extremely flammable aerosol per flame projection test

Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.

5. FIRE FIGHTING MEASURES

Special Fire-Fighting Procedures:

Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.

Hazardous Products of Combustion:

Oxides of carbon

Unusual Fire/Explosion Hazards:

Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.

Lower Explosive Limit:

2.6%

Upper Explosive Limit:

12.8%

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Eliminate all sources of ignition. Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C). Exposure to high temperatures may cause container to burst.

Handling:

Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Vapors may accumulate readily and may ignite explosively. Do not inhale vapors. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use in a well ventilated area. Avoid contact with skin and eyes. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear liquid

Odor:

Solvent

Boiling Point:

132°F - 300°F

pH:

Does not apply

Solubility in Water:

Slight

Specific Gravity:

0.8

VOC(Wt.%):

<45%

Vapor Pressure:

Not determined

Vapor Density (Air=1):

>1

Evaporation Rate:

>1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable at normal conditions

Hazardous Polymerization:

Will not occur

Incompatibilities:

Strong oxidizers, Amines, Sulfuric acid

Conditions to Avoid:

Keep away from heat, sparks and open flame. - No smoking

Hazardous Products of Combustion:

Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

Product Name: NON-CHLORINATED BRAKE & PARTS
CLEANER 14.5 OZ

Item No. 82220

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number: D001 as per 40CFR 261.21

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.1
UN Number: UN 1950

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

METHANOL, XYLENE

California Proposition 65: WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 3, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 3, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: March 13, 2013
Revision Number: 4