



Toll Free: 87 PERMATEx
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® RTV Silicone Dissolver

AAM Revised 02/12

PRODUCT DESCRIPTION

Permatex® RTV Silicone Dissolver easily removes silicone residue from flanges. RTV Silicone Dissolver is also effective on the Right Stuff® Gasket maker residue. The gel formula allows the technician to apply to residue, wait 5 minutes and wipe off residue. RTV Silicone Dissolver will not harm metal or plastic parts. OEM approved.

NOTE: Not recommended for use on non-silicone gasket residue.

PRODUCT BENEFITS

- Removes silicone residue
- Removes Right Stuff® gasket maker residue
- No grinding required

TYPICAL APPLICATIONS

- Removes silicone residue from valve covers, oil pans, timing covers, water pumps, differential covers, etc.
- Removes RTV formed-in-place gasket residue
- Removes RTV gasket residue from aluminum
- Removes RTV gasket residue from small, difficult to reach areas

DIRECTIONS FOR USE

CAUTION: May harm painted surfaces. Test before using.

1. Remove heavy silicone residues with Permatex® SaferScraper™ or a brass or plastic scraper.
2. Apply a bead of gel gasket remover to the residual silicone film, making sure that all of the silicone is covered.
3. Allow gasket remover to stand on the silicone for at least 5 minutes. (Removal time will vary based on silicone type and thickness.) Use scraper to lift dissolved silicone.
4. Wipe residue off with a dry rag.
5. Re-apply if necessary.
6. Prep flange for new gasket installation by cleaning with Permatex® Brake and Parts Cleaner.

For Cleanup

1. Wipe off excess Silicone Dissolver with a dry rag.
2. Clean hands with Permatex® brand hand cleaners.

PROPERTIES OF MATERIAL

Chemical Type
Appearance
Odor
Flash Point, °F
Specific Gravity

Typical Value
Organic acids
Amber gel
Solvent
15
0.79

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
80652	2.7 fl oz tube, carded

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **ITW Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEx, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEx, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-87PERMATEx)