



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

### Permatex® Windshield Deep Cleaning Wipe™

AAM Revised 04/13

#### PRODUCT DESCRIPTION

Permatex® Windshield Deep Cleaning Wipe is specially formulated to remove stubborn stains from automotive windshields. Strong cleaning agents and fine scrubbers eliminate stains that other glass cleaners cannot. It is also recommended to be used as a pretreatment before using silicone-based rain repellants.

#### PRODUCT BENEFITS

- Deep cleans windshield
- Removes silicone build up
- Use as a pretreatment prior to applying rain repellants
- Enhances drive safety
- Eliminates hard water spots
- Helps prolong wiper blade life
- Removes common stubborn stains such as bugs, mud, and road tar
- Reduces wiper blade chatter and streaking
- One pouch treats an entire windshield

#### TYPICAL APPLICATIONS

- Used for cleaning all exterior automotive windshields and glass
- This product is not for use on interior windows, plastic surfaces, window tint film, on mirrors, and on painted surfaces.

#### DIRECTIONS FOR USE

1. Pull both wiper blades away from the windshield and prop them up to remain away from windshield.
2. Open the Wind Shield Deep Cleaning wipe pouch and remove the towelette.
3. Using one side of the towelette, clean one half of the windshield by scrubbing hard in an overlapping circular motion, to ensure complete coverage of the area and making sure to keep the product off of all non-glass surfaces.
4. Repeat Step 3 using the reverse side of the towelette.
5. Hose product off of the windshield and any other surfaces that it has come into contact with, including painted surfaces and plastic trim.

#### For Cleanup

1. Clean off any residue that falls on the windshield, painted surfaces, and plastic trim by rinsing thoroughly with water, followed by wiping with a clean dry paper towel or cloth.
2. Clean hands with a Permatex brand hand cleaner.

#### PROPERTIES OF MATERIAL

Chemical Type  
Appearance

Odor  
Boiling Point °F

**Typical Value**  
Contains Petroleum Distillates  
Orange viscous liquid soaked into  
non-woven cloth  
Solvent  
212

#### GENERAL INFORMATION

**This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.**

**For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).**

#### ORDERING INFORMATION

Part Number	Container Size
09949	2.25" x 5" pouch

#### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

#### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.  
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.  
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX