



Toll Free: 87 PERMATEX  
(877-376-2839)

10 Columbus Blvd., Hartford,  
Connecticut 06106

6875 Parkland Boulevard, Solon  
Ohio 44139

## Technical Data Sheet

# Permatex® Grease Grabber Hand Cleaner

AAM Revised 12/10

### PRODUCT DESCRIPTION

Permatex® Grease Grabber™ Hand Cleaner is a natural, biodegradable hand cleaner containing no petroleum solvents. Grease Grabber contains no harsh solvents and utilizes soft polyolefinic scrubbers and a blend of surfactants to clean soiled hands. It is fortified with soothing emollients to moisturize and soften hands.

### PRODUCT BENEFITS

- Removes grease, hydraulic fluids, adhesives, asphalt, varnish, paint, carbon, tar, oils, soil, gasket cement, epoxies, glues and inks (rubber, water, oil, offset, flexo).
- Contains biodegradable surfactants.
- Won't clog drains.
- Contains skin conditioners to keep hands smooth
- Pleasant smelling formula
- Leaves hands smooth, not sticky.
- Withstands multiple heat/freeze cycles.
- Helps remove foul odors from hands

Grease Grabber Hand Cleaners have the special feature of cleaning without the use of petroleum solvents. The special scrubbers are made of a polyolefinic material that cleans hands and absorbs soils and odors while cleaning.

Grease Grabber is the ideal hand cleaner for the automotive, agriculture, mining, printing, construction, manufacturing, HVAC, marine, industrial and utility markets.

### DIRECTIONS FOR USE

1. Apply Grease Grabber to dry hands.
2. Rub into dirt embedded areas.
3. Add a small amount of water while cleaning.
4. Rinse with water and dry.

### PHYSICAL PROPERTIES

	Typical Value
Chemical Type	Surfactants, PE scrubbers
Appearance	Green, yellow paste
Odor	Lemon/Lime, Coconut
VOC (Wt %)	2
Flash Point, °F	>200
pH	8.6

### GENERAL INFORMATION

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

### ORDERING INFORMATION

Part Number	Container Size
13106	Lemon/Lime, 4 lb. tub
13112	Lemon/Lime, 12 oz. tub
14106	Coconut, 4 lb. tub
14112	Coconut, 12 oz. tub

### STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range. To prevent contamination of unused product, do not return any material to its original container.

### NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.

THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.

PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.  
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX