



Toll Free: 87 PERMATEX
(877-376-2839)

10 Columbus Blvd., Hartford,
Connecticut 06106

6875 Parkland Boulevard, Solon
Ohio 44139

Technical Data Sheet

Permatex® Brake Rotor Wipe™

AAM Revised 02/15

PRODUCT DESCRIPTION

Permatex® Brake Rotor Wipe is a water-based cleaner with no VOC's that cleans and protects against corrosion. It combines state-of-the-art cleaners and surfactants, with ferrous and non-ferrous metal (i.e. copper) corrosion inhibitors in a stable aqueous solution. This combination cleans new brake rotors quickly, leaving behind a thin corrosion-protection coating which prolongs rotor life.

PRODUCT BENEFITS

- Removes oil and impurities from the rotor surface
- Promotes pad wear-in and improved performance
- Cleans and protects rotors from corrosion
- Contains no VOC's
- Prevents brake squeal
- Can be used to clean other brake parts such as cables, bolts, etc.
- Each pouch treats one rotor

TYPICAL APPLICATIONS

- Used for cleaning new brake rotors

DIRECTIONS FOR USE

1. Open the Brake Rotor Wipe pouch and remove the towelette.
2. Completely scrub the front and back of the rotor to remove all rust inhibitor coatings, metal debris, and oil film.
3. Allow the rotor to dry completely before assembling.

For Cleanup

1. Remove any excess material with a clean, dry paper towel or cloth.
2. Clean hands using a Permatex brand hand cleaner.

PROPERTIES OF MATERIAL

	Typical Value
Chemical Type	Water-based cleaner
Appearance	Amber-colored liquid soaked into non-woven cloth
Odor	Mild
Boiling Point °F	212

GENERAL INFORMATION

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected for use with chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Material Safety Data Sheet, (MSDS).

ORDERING INFORMATION

Part Number	Container Size
09948	2.25" x 5" pouch
26629	50 count tub

STORAGE

Products shall be ideally stored in a cool, dry location in unopened containers at a temperature between 8° and 28°C (46° and 82°F) unless otherwise labeled. Optimal storage is at the lower half of this temperature range.

NOTE

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. **Permatex, Inc. specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Permatex, Inc. products and disclaims any liability for consequential or incidental damages of any kind, including lost profits.** This product may be covered by one or more United States or foreign patents or patent applications.

NOT FOR PRODUCT SPECIFICATIONS.
THE TECHNICAL DATA CONTAINED HEREIN ARE INTENDED AS REFERENCE ONLY.
PLEASE CONTACT PERMATEX, INC., TECHNICAL SERVICE DEPARTMENT FOR ASSISTANCE AND RECOMMENDATIONS FOR YOUR SPECIFIC APPLICATION.
PERMATEX, INC., HARTFORD SQUARE NORTH, 10 COLUMBUS BOULEVARD, HARTFORD, CT 06106 PHONE - (1-877)PERMATEX