

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: WATER BOND EPOXY STICK 2 OZ.
Item No: 84331
Product Type: Epoxy

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component:	Weight%	ACGIH; TLV-TWA	OSHA PEL
MAGNESIUM SILICATE 14807-96-6	30-60	2 mg/m ³	20 mppcf
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN 25068-38-6	10-30	Not listed	Not listed
NEPHELINE SYENITE 37244-96-5	10-30	10 mg/m ³ TWA ACGIH	Not listed
GLASS OXIDE 65997-17-3	10-30	Not listed	Not listed
2,4,6- TRIS(DIMETHYLAMINOMETHYL)PH ENOL 90-72-2	<5	Not listed	Not listed
SILICA, QUARTZ 14808-60-7	0.1-1.0	0.025 mg/m ³	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May cause skin sensitization. May be harmful if swallowed.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Ingestion may cause nausea and vomiting. Overexposure may cause eye and skin redness. Repeated skin contact may cause allergic skin reactions.

Component:	Weight%	NTP	ACGIH Carcinogens	IARC Carcinogen
MAGNESIUM SILICATE 14807-96-6	30-60	male rat-some evidence, female rat- clear evidence, male mice-no evidence, female mice-no evidence	A4-Not classifiable as a human carcinogen	Group 3 Supplement 7, 1987 Monograph 42, 1987
SILICA, QUARTZ 14808-60-7	0.1-1.0		A2 - Suspected Human Carcinogen	Group 1; Monograph 68, 1997

Aggravated Medical Condition: Preexisting skin disorders.

4. FIRST AID MEASURES

Ingestion: If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200 F° (>93°C) SCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Firefighters should wear self-contained breathing apparatus and protective clothing to prevent all skin and eye contact

5. FIRE FIGHTING MEASURES

Hazardous Products of Combustion:

Oxides of carbon, Oxides of nitrogen, Oxides of sulfur, Metal oxide fumes

Unusual Fire/Explosion Hazards:

None.

Lower Explosive Limit:

N/D

Upper Explosive Limit:

N/D

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Scrape up and place in an appropriate waste container for disposal.

7. HANDLING AND STORAGE

Storage:

Store in a cool, dry area. Store below 100°F.

Handling:

Avoid contact with skin and eyes. Do not take internally. Wash thoroughly after handling. Discard contaminated leather gloves and shoes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:

Safety glasses.

Skin:

Neoprene or nitrile gloves recommended.

Ventilation:

Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Respiratory Protection:

An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Tan solid

Odor:

Pungent sulfur

Boiling Point:

Not applicable

pH:

N/AP

Solubility in Water:

Negligible

Specific Gravity:

1.95

VOC(Wt.%):

0

Vapor Pressure:

Nil

Vapor Density (Air=1):

>1

Evaporation Rate:

N/AP

10. STABILITY AND REACTIVITY

Chemical Stability:

Stable

Hazardous Polymerization:

Will not occur

Incompatibilities:

Strong oxidizers

Conditions to Avoid:

Excessive heat

Hazardous Products of Combustion:

Oxides of carbon, Oxides of nitrogen, Oxides of sulfur, Metal oxide fumes

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations**US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)**U.S. Department of Transportation - DOT - 49 CFR (Ground)****DOT Shipping Name:**

Not regulated

Hazard Class:

None

UN/ID Number:

None

IATA (Air)**Proper Shipping Name:**

Not regulated

Product Name: WATER BOND EPOXY STICK 2 OZ.

Item No. 84331

14. TRANSPORTATION INFORMATION

Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Proper Shipping Name: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

None

California Proposition 65: WARNING: This product contains chemicals known to the State of California to cause cancer

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 2, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 2, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: February 24, 2014
Revision Number: 2